



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



Pricing Administration Use Only				
HT-63364.01	01			8/5/2026
Quote Number	Quote Revision	Shop Order Number	Serial Number(s)	Date

Customer HY-TEC Stock
Base Model Part Number 36422.1
Specified Model Description AJB9 1040-1,.188 BBL, .3125 HDS, 25 PSI,185 F,42'

A. Vessel

1) Design

AJB9 1040-1, Aluminum, Pneumatic dry bulk, Interior ring, Non-code trailer.

Code: Non-code

Capacity: 1040 cubic feet, 3 hopper

Compartments: One

Shape: Round with 45 degree discharge hoppers. Internal ring with smooth exterior.

Shell Material: Aluminum, 5454H32 barrel, end cone, and upper hopper section.

Head Material: Aluminum, .3125

Operating Pressure: 25 PSI

Design Temperature: 185 Degrees F.

Overall Length: 42'-6"

Product: Cement and Various other Dry Products; to be compatible with the materials of construction.

B. Construction

1) Frame

Front: Aluminum extruded channel, bolted or integrated to center frame.

Rear: Aluminum extruded channel, bolted to center frame.

Center: Aluminum extruded channel.

Struts: Aluminum extruded struts, standard duty at both ends.

2) Manhole

3 MM4120, 20" cast aluminum cover, six long lever aluminum cam handles hold-downs with replaceable Nylon wear plates and dual stainless steel safety retainers, 4" collar.

Gasket: 3 White neoprene gasket in cover, non-toxic.



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



3) Manhole Hinge Location

Manhole covers hinged to curbside of trailer.

C. Other Barrel Information

1) Material Finish

Mill finish aluminum

D. Valving and Piping

1) Seal provisions

None

2) Discharge valves

3 * 5" BTI BlackMaxx #5B-795-501HD5N butterfly valve with composite fiber body, AlloMaxx disc and white MaxxLife FDA seat. Aluminum lever lock handle and 5-position throttle plate.

3) Discharge Piping

Discharge tee: 3 5" X 4" B.T.I. "Siphon Flow", cast aluminum. #BT-500-A

Piping: 4" Aluminum schedule 40 between hoppers, ending at last hopper.

Rear Discharge Pipe: 4" aluminum schedule 40 discharge, under the axles, ending at the rear of the trailer.

Pipeline connectors: 4" bolted groove type couplers mounted at rear of rear hopper and forward of first hopper with black gaskets. Black rubber hose with stainless steel clamps between hoppers.

Adaptor: * 4" aluminum weld-on male adaptor

Cap: 4" aluminum dust cap

4) Air inlet

* 3" Aluminum on roadside with front elbowed upward. One (1) 3" BTI Black Maxx butterfly valve with Allomaxx disc, and white seat. Food Grade.

Check valves: * Two 3" BTI Optima flanged check valves, one forward of first hopper, one near front of air inlet line.

Adaptor: 3" aluminum male adaptor.

Cap: None. Temporary plug for Shipping.

5) Aeration

* 3" Aluminum aeration line controlled by 3" Black Maxx butterfly valve with Allomaxx disc and white seat. Three (3) BTI aerators per hopper.

0.75 * Stainless steel hopper savers.(4 hoppers)

* 2" lightweight aeration ball valve, BTV-2AV-FTHB, for individual hopper aeration. (3 hoppers)

Location: Aeration mounted roadside.



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



6) Blowdown

Relief Valve: * 3" Aluminum pipe and 3" BTI BlackMaxx butterfly valve with composite fiber body, AlloMaxx disc and Maxxlife seat.
2" BTI quick coupler relief valve, BTVR-2650-25, in blowdown line. Relief valve to be accessible from ground level. Relief valve set at 25 PSI.

7) Top Air

None.

8) Gauges

Pressure: Liquid filled, one for line pressure, one for tank pressure, enclosed in aluminum gauge box with light, located roadside, ahead of rear fender, facing forward. Pressure gauge range 0-30 PSI.

9) Delivery Hose

None.

E. Walkway and Ladder

1) Walkway

Top center: Non-skid tape, full length of barrel
Toe rail: 1 1/4" aluminum pipe each side of walkway, full length

2) Ladder

Aluminum tubular with large step, bolt on
Ladder Location: Mounted at rear head, centered. With step below bumper.

F. Cabinet

1) Cabinet

None. No Cabinet installed.

G. Hose Carriers

1) Hose Carrier

Aluminum tube 8" diameter x 21' long. Tube to be mounted to the outer edge of brackets.
Hose Carrier Door: 8" aluminum door, at rear. Door hinged at bottom.
Carrier Location: Mounted curbside rear

H. Lights and Wiring

1) Lights

12-volt, Truck-Lite LED grommet mount lights. Combination center marker / turn signals, mounted on barrel frame.



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



2) Wiring

Plug-in style harness system.

3) Rear Lights

Enclosed in Aluminum light boxes.

- * 1 additional LED stop/turn/tail light. Total of 3 lights in each box - (Red/Red/Red is Std, unless noted otherwise).

Outside lights are red with center light to be amber turn.

4) Extra Lights

None

5) Nose box

Truck-Lite standard 7 way, J560 receptacle without circuit breakers.

6) Gladhands

Gladhand, Phillips Quick release.

I. Chassis

1) Upper 5th Wheel

5/16" Standard duty upper coupler with Heavy duty double hubbed kingpin.

Paint: Fifth wheel plate painted black.

2) Landing Gear

Jost A440, 2-speed, load bearing, telescopic, with swivel type sand shoe.

Bracing: Stainless steel, with cross brace.

Crank location: Crank handle located on roadside

Tire carrier: None.

3) Suspension

Hendrickson INTRAAX AAT23K tandem axle with 5.75" diameter Hendrickson integrated axles. Axle spacing to be determined by scale.

Dump valve: No dump valve installed

Lift Axle Control: None - no auto lift controls included

Hangers: Galvanized hangers with soft coat applied to axle and trailing arm. For use on aluminum subframe with bolt-on hangers.

Bumper: No bumper included

Under-ride Protection: None (no under ride required, Wheels back exempt.)



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



4) Axles

Beam:	Inverted axle/raised center NOTE: Axle diameter changes to 5" with this option.
Track:	Axle track, 71.5"
Hub & drums:	Hendrickson 5 year warranty, Ready to roll with Duralite hubs, cast drums and semi-fluid grease. OEM slack adjusters, seals, brake chambers and brake lining.

5) Brakes

Anti-lock / Roll stability:	Wabco 4S/2M with "RSS-Plus" roll stability support system for tandem (2) axle airride suspension set.
Air system:	One (1) aluminum tank system. 2850 cu. in. meeting FMVSS 121 D.O.T. specifications.

6) Emission Compliance

NA

7) Wheels

Original Equipment Manufacturer, 22.5 X 8.25 Aluminum polished wheels

8) Tires

Original Equipment Manufacturer, 11R-22.5, Load Range G 14 Ply.

9) Tire pressure system

No tire pressure system included.

10) Fenders

Front:	Aluminum, single contour, ribbed, front fender, each side.
Rear:	Aluminum, double contour, ribbed, rear fender, each side.

11) Mud flaps

* White anti-sail, anti-spray mudflaps with logo installed front and rear.

J. Hose hook

1) Hose hook

Adjustable hose hook mounted at front of trailer with 3" dummy adapter on curbside.

K. Jumper Hose

1) Jumper Hose

None.

L. TANK Ai™



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



1) IntelliSECURE

TANK Ai™ - None installed

M. Miscellaneous

1) Decals

Standard warning and safety package. Decals in English.

2) Conspicuity Tape

Discontinuous tape

3) Customer Logo

None

4) Document holder

Truck Lite 97960 Certificate Holder. Install in standard location unless otherwise specified.

5) Placards

None

6) Paint

None. No paint or primer installed on trailer.

7) Interior Cleaning

Class I, as welded. Not intended for food grade or plastic products. Note: Interior cleaning is recommended prior to initial loading to avoid possible product contamination.

8) Warranty

* Heil Trailer Silver Warranty Package.

9) Tests

Standard testing.

10) Drawings

None.



HIGHWAY TRANSPORTATION EQUIPMENT COMPANY, INC

51 Industrial Circle Lancaster PA 17601

Phone (717)656-4329 FAX (717)656-4238



Order Acceptance Form

Model : 1040 Cu. Ft. AJB9 Cementer Pneumatic - 3 Hoppers

Sales Rep. : Matt Leed ... PHONE: 717-656-4329 ext. 112
E-MAIL: matt@hytectank.com

Ship To : HY-TEC
51 Industrial Circle
Lancaster PA 17061

End User : HY-TEC Stock

Item Price	:	75,300.00
F.E.T.*	:	9,756.00
State Tax	:	0.00
Shipping	:	6,000.00
Total Price	:	91,056.00
Total Weight	:	+/-3%

Quote Name: HY-TEC Stock

Quote Date: 8/5/2026 (Quote is valid for 30 days from this date)

Delivery schedule subject to plant approval.

This quotation is subject to the terms and conditions which can be viewed on our website:

www.heiltrailer.com

CUSTOMER PICKUP OF COMPLETED UNITS

- In the case of a customer pickup, customer agrees to pick up the unit within three (3) calendar days following completion. If after the three (3) calendar days the customer has not picked up the units, customer requests Heil Trailer International, Co. to deliver the unit to the designated off-site storage area and authorizes Heil Trailer International, Co. to store the unit until it is picked up by the customer.

F.E.T. is 12% of the Item Price less the F.E.T. tire credit. Local fees and local use taxes are also not included.

Order Confirmation:

Order Review:

Customer

Date

Distributor

Date